

LINEAR²

Granular Water Treatment

Treatment Functions and Advantages of using Linear² :

Linear² is a linear chain polyphosphate manufactured specifically to resist reversion or hydrolytic chemical breakdown. This specialty polyphosphate is produced with a high P₂O₅ percentage to provide extended use. This product is produced to be stable under otherwise extreme conditions of temperature, time and where the requirements of potability must be met

- ▶ Linear² is a unique polyphosphate that is a specialty glass, with a P₂O₅ at the very high end of the range utilizing the benefits of a stable long molecular chain polyphosphate. This makes it especially useful in circulating water systems which must have a long shelf or use life.
- ▶ Linear² has 1/3+ slower reversion rate compared with standard hexametaphosphate which makes it a more stable treatment and has longer use life.
- ▶ Maintains water clarity through functional sequestration of minerals and scale control - resulting in fewer customer water complaints and reduced flushing requirements.
- ▶ Reduced corrosion through cathodic “deadening” of the corrosion cell potential thereby inhibiting corrosion through out the water distribution plumbing.
- ▶ Reduces the demand for chlorine/chloramines because of the stabilization of minerals and reduction of scale deposits - effectively improving disinfection throughout the water distribution system.
- ▶ Gradual removal and inhibition of mineral scale deposits formations in hot water lines and residential water heaters.
- ▶ Since Linear² is manufactured with highly stable protocol, the formulation of liquid concentration at the project site for injection remains effective over longer periods of time than standard phosphate treatments.

Linear² Chemical Properties and Certification:

- **Composition:** Powders and granules
- **Bulk Density:** 79 lbs./cubic feet
- **% P₂O₅ - Blended:** 69.6
- **NaO/P₂O₅ :** 1.00
- **Average Chain Length :** 23.3



- **Appearance:** Clean, white
- **pH of 1% solution:** 5.6 - 6.7
- **Specific gravity:** 1.2
- **Solubility:** 3.0 lbs/gal +
- **NSF max potable dosage:** 12 mg/L

Linear² Application and Dosage:

Linear² granular polyphosphate can be applied to a water system using a chemical injection metering pump once liquified with water. Linear² goes easily into solution with agitation in concentrations of up to 3 lbs. per gallon of water. Typical potable treatment dosages range from 0.75 to 3.75 and higher for non-potable water systems.

Packaging, Shipping and Handling of Linear²:

Linear² granular is packaged in 50 and 300 pound containers FOB Clearwater, FL 33760. Linear² is shipped in securely tagged and sealed containers. Please refer to MSDS for handling information.



For more complete information on properties and safe handling of this material, see the SPER Chemical Material Safety Data Sheet [MSDS].

NOTICE

The information herein is to our knowledge true and accurate. All information appearing on this document is based on data obtained from the manufacturer and/or recognized technical sources. Because of conditions beyond our control, we make no warranty or representation, expressed or implied, except that the product discussed herein conform to the chemical descriptions shown on their labels/product data. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will SPER Chemical Corporation be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the product to which the information refers. No agent, representative or employee of this company is authorized to vary any of the terms of this notice.